


0.3 mm Pitch, 0.65 mm Height, Top Contact, Back-Flip FPC Connectors

FH42 Series



0.65 mm height




Fig.1

■ Features

1. Space saving 0.3 mm pitch and low-profile top contact connector

This top contact connector delivers a 0.65 mm height, mounting depth of 3.08 mm and depth 3.55 mm with the actuator closed. All of this helps to maximize PCB space.

2. FPC retention secured, despite the low profile

Improved FPC horizontal retention by reinforcing the clasp temporary retention mechanism.

3. Reduces production costs

The actuator is delivered in the open position and allows you to immediately insert the FPC.

4. Favorable FPC insertion, despite the low profile

- The unique clasp form means an audible click when the FPC goes over the clasp, while also preventing incorrect (diagonal) insertion of FPC.

- Despite the temporary retention mechanism of the reinforcing clasp, horizontal insertion of FPC is possible.

5. Insertion check window

There is a cutout on the housing that allows you to visually inspect the FPC to make sure that it is locked into place, preventing incorrect insertion of the FPC.

6. Accepts 0.12 mm thick FPC

The connector accepts 0.12 mm thick FPC, standard thickness for 0.3 mm pitch low-profile connectors.

7. Fully molded structure aids PCB layout

The bottom of this connector is enclosed by a fully molded structure that protects the contacts and removes any restrictions from PCB patterning and layout design.

8. Halogen-free

The connector does not use chlorine and bromine exceeding standard limits.

Defined in accordance with IEC61249-2-21 Br: 900 ppm max, Cl: 900 ppm max, Br + Cl: 1,500 ppm max.

9. Supports automatic pick-n-place mounting

Offered in tape and reel packaging that is compatible with automatic machine mounting. (5,000 pieces per reel). The standard packaging is 5,000 pieces per reel, but it is also offered in a 500 piece reel. (The outer diameter of the reel will be ϕ 180 mm in this case.)

FPC insertion




Fig.2

With actuator locked





Fig.3



Product Specifications

Ratings	Current rating 0.2 A(Note1)	Operating temperature range:-55 to +85°C (Note 2)	Storage temperature range:-10 to +50°C (Note 3)
	Voltage rating 30 Vrms AC	Operating humidity range:Relative humidity 90% max. (No condensation)	Storage humidity range:Relative humidity 90% max. (No condensation)

Recommended FPC SPC	t=0.12 ± 0.02 mm, Gold plated
---------------------	-------------------------------

Item	Specification	Conditions
1.Insulation resistance	50 MΩ min.	100 V DC
2.Withstanding voltage	No flashover or insulation breakdown	90 Vrms AC / one minute
3.Contact resistance	200 mΩ max. * Including FPC conductor resistance	1 mA, AC max (AC: 1kHz)
4.Durability	Contact resistance: 200 mΩ max. No damage, cracks and looseness of parts	10 cycles
5.Vibration	No electrical discontinuity of 1 μs or longer Contact resistance: 200 mΩ max. No damage, cracks and looseness of parts	Frequency: 10 to 55 Hz, Half amplitude of 0.75mm, for 10 cycles in 3 axial directions
6.Shock	No electrical discontinuity of 1 μs or longer Contact resistance: 200 mΩ max. No damage, cracks and looseness of parts	981m/s ² , Duration of pulse 6ms at 3 times in 3 both axial directions
7.Humidity (Steady state)	Contact resistance: 200 mΩ max. Insulation resistance: 50 MΩ min. No damage, cracks and looseness of parts	96 hours at 40°C and humidity of 90 to 95%
8.Temperature cycle	Contact resistance: 200 mΩ max. Insulation resistance: 50 MΩ min. No damage, cracks and looseness of parts	Temperature : -55°C → +15°C to +35°C → +85°C → +15°C to +35°C Time: 30 → 2 to 3 → 30 → 2 to 3 minutes 5 cycles
9.Resistance to soldering heat	No deformation of case of excessive looseness of the terminal	Reflow: Recommended temperature profile Manual soldering: 350°C ±10°C for 5 seconds

(Note 1) When electrifying rated current to all contacts, use 70% of rated current.

(Note 2) Including temperature rise caused by current flow.

(Note 3) The term "storage" refers to the long-term storage condition of unused products before PCB mount. Operating temperature and humidity ranges shall apply to unpowered products after PCB mount.

Materials

Parts	Material	Color/Finish	Remarks
Insulator	LCP	Beige	UL94V-0
	PA	Black	UL94HB
Contacts	Phosphor bronze	Gold plated	—
Metal fittings		Pure tin reflow plated	—


Ordering information

FH 42 - 31S - 0.3 SHW (10)


① ② ③ ④ ⑤ ⑥

① Series name: FH	⑤ Terminal type SHW: SMT horizontal staggered mounting type
② Series No. : 42	⑥ Specifications
③ No. of contacts: 11, 15, 19, 23, 31, 41	(10) Gold plated with nickel barrier, 5,000 pieces per reel
④ Contact pitch: 0.3 mm	(99) Gold plated with nickel barrier, 500 pieces per reel

Connector Dimensional Drawing



Detailed drawing of B




- Notes
1. The dimension in parentheses are for reference.
 2. Lead co-planarity including reinforced metal fittings shall be 0.1mm max.
 3. To be delivered with tape and reel packages, see attached packing specifications for details.
 4. Note that preventive hole for sink mark or slit could be added for improvement.
 5. The quality remains good, even with the dark spots, which could occasionally occur on molded plastic.
 6. The color of the plating may change after the reflow process, but it will not negatively affect the performance of these connectors.
 7. This product satisfies halogen-free requirements defined as 900ppm maximum chlorine, 900ppm maximum bromine, and 1500ppm maximum total of chlorine and bromine.

Unit: mm

Part No.	HRS No.	No. of Contacts	A	B	C	D	E
FH42-11S-0.3SHW(**)	580-2306-0 **	11	5.4	2.4	3	4.15	4.88
FH42-15S-0.3SHW(**)	580-2302-0 **	15	6.6	3.6	4.2	5.35	6.08
FH42-19S-0.3SHW(**)	580-2305-8 **	19	7.8	4.8	5.4	6.55	7.28
FH42-23S-0.3SHW(**)	580-2309-9 **	23	9	6	6.6	7.75	8.48
FH42-31S-0.3SHW(**)	580-2301-7 **	31	11.4	8.4	9	10.15	10.88
FH42-41S-0.3SHW(**)	580-2304-5 **	41	14.4	11.4	12	13.15	13.88

(Note) This product is packaged on tape and reel and is only sold in full reel quantities of either 5,000 or 500 piece reels. Please place orders by full reel quantities.

Recommended Stencil Pattern




Unit: mm

Part No.	HRS No.	No. of Contacts	B	C	D
FH42-11S-0.3SHW(**)	580-2306-0 **	11	2.4	3	4.15
FH42-15S-0.3SHW(**)	580-2302-0 **	15	3.6	4.2	5.35
FH42-19S-0.3SHW(**)	580-2305-8 **	19	4.8	5.4	6.55
FH42-23S-0.3SHW(**)	580-2309-9 **	23	6	6.6	7.75
FH42-31S-0.3SHW(**)	580-2301-7 **	31	8.4	9	10.15
FH42-41S-0.3SHW(**)	580-2304-5 **	41	11.4	12	13.15

[illegible]

Part No.	HRS No.	No. of Contacts	B	C	F	G	H
FH42-11S-0.3SHW(**)	580-2306-0 **	11	2.4	3	4.85	3.82	5.8
FH42-15S-0.3SHW(**)	580-2302-0 **	15	3.6	4.2	6.05	5.02	7
FH42-19S-0.3SHW(**)	580-2305-8 **	19	4.8	5.4	7.25	6.22	8.2
FH42-23S-0.3SHW(**)	580-2309-9 **	23	6	6.6	8.45	7.42	9.4
FH42-31S-0.3SHW(**)	580-2301-7 **	31	8.4	9	10.85	9.82	11.8
FH42-41S-0.3SHW(**)	580-2304-5 **	41	11.4	12	13.85	12.82	14.8

Single-sided FPC




Material Name	Materials	Thickness (μm)
Covering film layer	Polyimide 1 mil	(25)
Cover adhesive		(25)
Surface treatment	1 μm to 5 μm Nickel underplated 0.2 μm Gold plated	3.2
Copper foil	Cu 1/2 oz	18
Base adhesive	Heat-Hardened adhesive	Non-adhesive type
Base film	Polyimide 1 mil	25
Reinforcement material adhesive	Heat-Hardened adhesive	35
Stiffener	Polyimide 2 mil thick	50
	Total	131.2


HRS 5

◆ Packaging Specifications


● Embossed carrier tape dimension (Tape width: 24mm MAX)




● Embossed carrier tape dimension (Tape width: 32mm MIN)



● Reel dimensions



● Leader, Trailer Dimension




Unit: mm

Part No.	HRS No.	No. of Contacts	J	K	L	N	P
FH42-11S-0.3SHW(**)	580-2306-0 **	11	16	—	7.5	17.4	21.4
FH42-15S-0.3SHW(**)	580-2302-0 **	15	24	—	11.5	25.4	29.4
FH42-19S-0.3SHW(**)	580-2305-8 **	19	24	—	11.5	25.4	29.4
FH42-23S-0.3SHW(**)	580-2309-9 **	23	24	—	11.5	25.4	29.4
FH42-31S-0.3SHW(**)	580-2301-7 **	31	24	—	11.5	25.4	29.4
FH42-41S-0.3SHW(**)	580-2304-5 **	41	24	—	11.5	25.4	29.4

◆ Temperature Profile

●Using Pb-free solder paste



Conditions applied

Reflow method : IR/Hot air
Reflow environment : Room air
Solder paste : Paste type Sn/3.0Ag/0.5Cu (M705-GRN360-K2-V from Senju Metal Industry)
Test PCB : Materials and size
Glass epoxy 25×50×0.8 mm
Land dimension 0.28×0.6, 0.28×0.9 mm
Stencil : Thickness 0.1 mm
Slot size 0.26×0.48, 0.26×0.73 mm

This solder profile is based on the conditions provided above.

Please check the mounting conditions before use, conditions such as solder paste types, manufacturer, PCB size and any other soldering materials may alter the performance of such materials.

Connector Operation and Precautions

[Operation]


This connector needs to be handled with care due to its thin design and miniature stature. Please refer to the following descriptions for handling precautions.

1. Initial condition

- ① Actuator does not have to be operated before inserting FPC, as the connector is delivered with the actuator opened.

[Notes]

- Do not close the actuator before inserting FPC.
- Closing the actuator without FPC could make the contact gap smaller, which could increase the FPC insertion force.




2. How to insert FPC

- ① Insert the FPC into the connector opening horizontally to the PCB plane. Insert it properly to the very end.

[Notes]

- Insert the FPC with actuator opened.
- Do not twist the FPC to up and down, right and left or an angle.





3. FPC insertion check

Metal fittings guide the FPC tabs to the correct position.


Make sure that the FPC tabs are located in proper position as shown in the figure below after FPC insertion.

[Notes]


- Do not insert the FPC at an angle and / or stop it before insertion is completed.



Correct insertion



Diagonal insertion



Partial insertion

[Operation]

4. How to lock


- ① Push down the actuator a rotating motion.

Rotate and flat down the central or entire part of the actuator completely with the ball of a finger.
(Do not push up only one side of the actuator. The actuator can be twisted causing damage.)


* Do not apply excessive force to the housing during any operation.




Rotate



Do not apply excess force to the housing during the operation.



Close the actuator at the center



Do not operate the actuator at one end only.


5. How to remove FPC (How to unlock)

- ① After rotating the actuator to the fully opened position carefully withdraw the FPC pulling out at 30 degree angle to the PCB mounting surface.


(Do not lift up only side of actuator the actuator can be twisted causing damage)

* The actuator is opened up to the movable limit, 90 degree.


Do not open the actuator beyond the specified degree or apply excess force to the actuator.




Rotate




Apply weight the direction as shown in the figure. Try open more than 90°



Operate the center



Operate only one side



image

* This connector utilizes a back flip system; the actuator is placed on the side opposite of the FPC insertion opening. Do not attempt to open the actuator from the FPC insertion side.


[Operation]

6. FPC routing after connection

- ① Depending on a FPC rounding, a load is applied to the connector, and a contact failure may occur. To prevent a failure, take the following notes into a consideration during mechanism design.

[Notes]

- Make sure that FPC and stiffener do not contact chassis.
- Avoid applying forces to FPC in vertical or horizontal directions.
In addition, avoid pulling up and down on the FPC.
- When fixing FPC after FPC cabling, avoid pulling FPC, and route the wire FPC with slack.
In this regard, the stiffener is parallel to the PCB.
- Do not mount other components touching to the FPC underneath the FPC stiffener.



[Precautions when mounting PCB]

◆ Warp of PCB

Minimize warp of the PCB as much as possible.

Lead co-planarity including reinforced metal fittings is 0.1 mm or less.

Too much warp of the PCB may result in a soldering failure.

◆ Flexible board design

Please make sure to put a stiffener on the backside of the flexible board.

We recommend a glass epoxy material with the thickness of 0.3mm MIN.

◆ Load to connector

Do not add 0.5N or greater external force when unreel or pick and place the connector etc, or it may get broken.

In addition, do not insert the FPC or operate the connector before mounting.


◆ Load to PCB

- Splitting a large PCB into several pieces

- Screwing the PCB

Avoid the handling described above so that no force is exerted on the PCB during the assembly process.

Otherwise, the connector may become defective.



◆ Instructions on manual soldering

Follow the instructions shown below when soldering the connector manually during repair work, etc.

① Do not perform manual soldering with the FPC inserted into the connector.

② Do not heat the connector excessively. Be very careful not to let the soldering iron contact any parts other than connector leads. Otherwise, the connector may be deformed or melt.

③ Do not supply excessive solder(or flux).

If excessive solder(or flux) is supplied on the terminals, solder or flux may adhere to the contacts or rotating parts of the actuator, resulting in poor contact or a rotation failure of the actuator.

Supplying excessive solder to the metal fittings may hinder actuator rotation, resulting in breakage of the connector.

USA:

HIROSE ELECTRIC (U.S.A.), INC. HEADQUARTERS
2688 Westhills Court, Simi Valley, CA 93065-6235
Phone : +1-805-522-7958
Fax : +1-805-522-3217
<http://www.hirose.com/us/>

USA:

HIROSE ELECTRIC (U.S.A.), INC. DETROIT OFFICE (AUTOMOTIVE)
37677 Professional Center Drive, Suite #100C
Livonia, MI 48154
Phone : +1-734-542-9963
Fax : +1-734-542-9964
<http://www.hirose.com/us/>

GERMANY:

HIROSE ELECTRIC EUROPE B.V. NUERNBERG OFFICE
Muggenhofer Str. 136 90429 Nuernberg
Phone : +49-911 32 68 89 63
Fax : +49-911 32 68 89 69
<http://www.hirose.com/eu/>

CHINA:

HIROSE ELECTRIC (SHANGHAI) CO.,LTD. BEIJING BRANCH
A1001, Ocean International Center, Building 56# East 4th
Ring Middle Road, ChaoYang District, Beijing, 100025
Phone : +86-10-5165-9332
Fax : +86-10-5908-1381
<http://www.hirose.com/cn/>

TAIWAN:

HIROSE ELECTRIC TAIWAN CO., LTD.
103 8F, No.87, Zhengzhou Rd., Taipei
Phone : +886-2-2555-7377
Fax : +886-2-2555-7350
<http://www.hirose.com/cn/>

INDIA:

HIROSE ELECTRIC SINGAPORE PTE. LTD. DELHI LIAISON OFFICE
Office NO.519, Regus-Green Boulevard, Level5, Tower C,
Sec62, Plot B-9A, Block B, Noida, 201301, Uttar Pradesh, India
Phone : +91-12-660-8018
Fax : +91-120-4804949
<http://www.hirose.com/sg/>

USA:

HIROSE ELECTRIC (U.S.A.), INC. SAN JOSE OFFICE
3255 Scott Boulevard, Building 7, Suite 101
Santa Clara, CA 95054
Phone : +1-408-253-9640
Fax : +1-408-253-9641
<http://www.hirose.com/us/>

THE NETHERLANDS:

HIROSE ELECTRIC EUROPE B.V.
Hogehillweg #8 1101 CC Amsterdam Z-O
Phone : +31-20-6557460
Fax : +31-20-6557469
<http://www.hirose.com/eu/>

UNITED KINGDOM:

HIROSE ELECTRIC EUROPE BV (UK BRANCH)
4 Newton Court, Kelvin Drive, Knowlhill,
Milton Keynes, MK5 8NH
Phone : +44-1908 202050
Fax : +44-1908 202058
<http://www.hirose.com/eu/>

CHINA:

HIROSE ELECTRIC TECHNOLOGIES (SHENZHEN) CO., LTD.
Room 09-13, 19/F, Office Tower Shun Hing Square, Di Wang Commercial Centre,
5002 Shen Nan Dong Road, Shenzhen City, Guangdong Province, 518008
Phone : +86-755-8207-0851
Fax : +86-755-8207-0873
<http://www.hirose.com/cn/>

KOREA:

HIROSE KOREA CO., LTD.
1261-10, Jeoungwhang-Dong, Shihung-City,
Kyunggi-Do 429-450
Phone : +82-31-496-7000,7124
Fax : +82-31-496-7100
<http://www.hirose.co.kr/>

INDIA:

HIROSE ELECTRIC SINGAPORE PTE. LTD. BANGALORE LIAISON OFFICE
Unit No.03, Ground Floor, Explorer Building International Tech
Park Whitefield Road, Bangalore 560066 Karnataka, India
Phone : +91-80-4120 1907
Fax : +91-80-4120 9908
<http://www.hirose.com/sg/>

USA:

HIROSE ELECTRIC (U.S.A.), INC. CHICAGO OFFICE
580 Waters Edge Lane, Suite 205 Lombard IL
60148
Phone : +1-630-282-6706
Mail : inquiries@hirose.com
<http://www.hirose.com/us/>

GERMANY:

HIROSE ELECTRIC EUROPE B.V. GERMAN BRANCH
Herzog-Carl-Strasse 4 D-73760 Ostfildern
(Scharnhäuser Park)
Phone : +49-711-4560-02-1
Fax : +49-711-4560-02-299
<http://www.hirose.com/eu/>

CHINA:

HIROSE ELECTRIC (SHANGHAI) CO., LTD.
1601, Henderson Metropolitan, NO.300, East Nanjing
Road, Huangpu District, Shanghai, China 200001
Phone : +86-21-6391-3355
Fax : +86-21-6391-3335
<http://www.hirose.com/cn/>

HONG KONG:

HIROSE ELECTRIC HONGKONG TRADING CO., LTD.
Room 1001, West Wing, Tsim Sha Tsui Centre, 66
Mody Road, Tsim Sha Tsui East, Kowloon, Hong Kong
Phone : +852-2803-5338
Fax : +852-2591-6560
<http://www.hirose.com/hk/>

SINGAPORE:

HIROSE ELECTRIC SINGAPORE PTE. LTD.
10 Anson Road #26-1, International Plaza
079903, Singapore
Phone : +65-6324-6113
Fax : +65-6324-6123
<http://www.hirose.com/sg/>

MALAYSIA:

HIROSE ELECTRIC SINGAPORE PTE. LTD. (REPRESENTATIVE OFFICE)
1-10-07, Suntech @ Penang Cybercity (1164), Lintang
Mayang Pasir 3,11950, Bayan Baru, Penang, Malaysia.
Phone : +604-619-2564
Fax : +604-619-2574
<http://www.hirose.com/sg/>



HIROSE ELECTRIC CO.,LTD.

2-6-3,Nakagawa Chuoh,Tsuzuki-Ku,Yokohama-Shi 224-8540,JAPAN
TEL: +81-45-620-3526 Fax: +81-45-591-3726
<http://www.hirose.com>
<http://www.hirose-connectors.com>